

23HDX Equipment Specifications

Length: 48' Height: 13'3" Width: 8'6" with ability to expand to: 12'6"



23HDX Equipment Specifications

Production

- Grass Valley HD Kayenne switcher
- 4.5 M/Es, 96 inputs/48 outputs
- Internal Image Store
- 4 iDPMs/2 eDPMs
- 4 Stripe (M/E) control panel
- Up to 90 images in production wall

Cameras/ Lenses & Support

- 8 Grass Valley LDX 80 Premier 720p/1080i triax cameras
- Canon 75x9.3 long lens
- 5 Canon 72x9.3 long lenses
- Canon YJ18x9B ENG lens
- Canon KJ17Ex7.7B ENG lens
- Canon HJ11ex4.7B ENG lens
- Studio Config Kit with LCD VF
- 6 Grass Valley SuperExpander sleds long lens adapters
- 6 Vinten Vector 70 heavy duty pan/tilt heads
- 6 Mathews MT1 heavy duty tripods
- 3 Gitzo ENG tripods with Libec H85 pan/tilt heads
- 2 SD LPS clock cameras

Replay, Spotbox and Edit Systems

- Three 6 Channel XT3 full editing units 4 inputs/ 2 outputs
- Codecs supported:
 - M-JPEG – User selectable bitrate 20-360Mbps
 - Avid DNxHD® (120/145Mbps)
 - Avid DNxHD® High Level (185/220Mbps, 8-bit and 10-bit)
 - VC-3 (SMPTE 2019-1; Avid-compatible) 100Mbps
 - Apple ProRes® 4:2:2 (120/145Mbps)
 - Apple ProRes® 4:2:2 HQ (185/220Mbps)
 - Apple ProRes® 4:2:2 LT (85/102Mbps)
 - MPEG-2 intra – User selectable bitrate 20-360Mbps
 - DVCPRO HD
 - AVC-Intra Class 100
 - XAVC-Intra Class 100
- 8 Channel K2 Summit with Dyno for instant replay of two 6x SSMO cameras (With file transfer of clips of EVS network)
- 4 Channel EVS XS server for Spotbox
- Lance TDC-100 Disk Controller
- XFile3 with USB 3.0
- GigE network available
- 2 DVD player/recorders
- Up to 4 replay operator positions

Audio

- CALREC Artemis Beam Audio Mixer (56 fader) 164 routable inputs via MADI, 64 analog inputs/48 analog outputs
- ·RTW TM7 audio scope
- Audio Board can output multiple channels of surround sound (Upon request)
 - Encoders for surround sound are the clients responsibility
- Enco Hotshot2 Audio Playout System
- Digicart E with ZIP drive
- CD Player
- 7 Sennheiser ME-67 long shotgun mics
- 5 Sennheiser ME-66 short shotgun mics
- 5 RE 50 stick mics
- 5 EV 635 stick mics
- 4 MD-46 stick mics
- 5 Sony ECM77B lavalier mics
- 7 Sennheiser HMD sportscaster headsets
- 6 Daltech talkback boxes
- 6 DT12 Breakout Boxes
- 10 DT12 fanout
- 4 Fostex portable speakers
- Fiber Booth Kit (Upon request)
- Parab dishes (Upon request)

Communications

- Telex 80-port Cronus intercom
- 12 Channels of IFB
- 10 Channels of PL
- 18 Telex 325 intercom beltacks
- 11 Telex 4030 IFB beltacks
- 4 Telos One Interface
- 3 RTS TIF 2000As
- 12 Line NEC phone system
- 6 Two-Way Radios with 2 base stations

Graphics

- For- A Telestrator with HD touchscreen

Engineering & Misc

- 128x256 Grass Valley HD- SDI Video Router
- 14 Frame sync/cross converters
 - 6 AIA FS-1s, 6 AIA FS-2s, 2 Harris X-50s for a total of 20 paths
- TSI-1000 tally system with virtual tally
- 10 Utility HD to SDI/NTSC downconverters
- 2 Lighting Kits

Outboard Monitors

- Eleven 15" LCD portable field monitors

Cable

- 5000' Triax
 - Four 500', Ten 250', Five 100'
 - One 6 line triax 175'
- 250' 10 Line video mult
 - One 125', One 75', One 50'
- 450' TAC singlemode fiber
 - Two 150' TAC-12, One 150' TAC-6
- 2000' DT12
 - Five 250', Five 150'
- 225' Three phase power cable
 - Sets of 100', 75', and 50'
- Additional cable available if shipped separately

Power Required

- 208 VAC, three phase, 200 amps
 - Separate 200 amps of three phase 208 VAC may be required in high heat locations