


## 31 HDX Equipment Specifications

Length: 53' Height: 13'3" Width: 8'6" with ability to expand to: 13'8"



# 31 HDX Equipment Specifications

## Production

- Grass Valley HD Kayenne switcher
- 4.5 M/Es, 96 inputs/48 outputs
- Internal Image Store
- 8 iDPMs/4 eDPMs
- 4 Stripe (M/E) Contol Panel
- 2 Stripe (M/E) secondary switcher
- Up to 90 images in production wall

## Cameras/ Lenses & Support

- 7 Grass Valley LDX 80 Premier 720p/1080i triax cameras
- 4 Grass Valley LDX86 universe super slow mo fiber cameras (Upon request. Can be used as regular live cameras)
- 4 Grass Valley 3G fiber converters (SHEDS)
- 9 Canon 72x9.3 long lenses
- 4 Canon XA17x7.6 ENG lenses
- Four 2" ENG VFs
- 2 Panasonic AG-HPX370 fiber cameras with lenses and tripods (2 Single mode fibers per camera required) (Booth)
- 9 Grass Valley RefleX SuperExpander sleds with 7" VFs
- 9 Vinten Vector 75 heavy duty pan/tilt heads
- 9 Mathews MT1 heavy duty tripods
- 4 Gitzo ENG tripods with Libec H85 pan/tilt heads
- 2 SD LPS clock cameras

## Replay, Spotbox and Edit Systems

- Two 12 Channel EVS XT3 full editing units
- Two 6 Channel EVS XT3 full editing units 4 inputs/2 outputs
- 4 Channel EVS XT3 Replay Only units 2 inputs/2 outputs
- 4 Channel EVS XS server for Spotbox (2 Channels per show during dual feeds)
- Codecs supported:
  - M-JPEG – User selectable bitrate 20-360Mbps
  - Avid DNxHD® (120/145Mbps)
  - Avid DNxHD® High Level (185/220Mbps, 8-bit and 10-bit)
  - VC-3 (SMPTE 2019-1; Avid-compatible) 100Mbps
  - Apple ProRes® 4:2:2 (120/145Mbps)
  - Apple ProRes® 4:2:2 HQ (185/220Mbps)
  - Apple ProRes® 4:2:2 LT (85/102Mbps)
  - MPEG-2 intra – User selectable bitrate 20-360Mbps
  - DVCPRO HD
  - AVC-Intra Class 100
  - XAVC-Intra Class 100
- 4 Channel Grass Valley K2 Solo
- 2 Lance TDC-100 Disk Controllers
- 2 XFile3s with USB 3.0
- GigE network available
- 2 DVD recorders/players
- Panasonic P2 Deck AG-HPD24P
- Up to 6 replay operator positions

## Audio

- CALREC Artemis Beam Audio Mixer/Router (48 fader) 128 analog/128 analog outputs, inputs, 64 AES inputs/64 AES outputs
- Audio Board can output multiple channels of surround sound
  - Encoders for transmitting surround sound are the clients responsibility
- Enco Hotshot2 audio playback system
- Digicart E with ZIP drive
- CD Player
- 6 Audio Technica BP4073 short shotgun mics
- 6 Sennheiser MKH 70 P48(long shotguns mics
- 5 Sennheiser MD-46 stick mics
- 7 Sony ECM77B lavaliers
- 5 Sony ECM55B lavaliers
- 5 Crown PCC-160 Cardioid Microphones
- 8 Sennheiser HMD sportscaster headsets
- 6 Daltech talkback boxes
- Videotek ASM-100 audio scope
- 6 DT12 Breakout Boxes
- 10 DT12 fanouts
- 6 Fostex portable speakers
- Fiber Booth Kit (Upon request)
- Parab dishes (Upon request)

## Communications

- RTS ADAM Matrix System
- 96 Analog ports, 16 ports of RVON
- 12 Channels of IFB
- 12 Channels of PL
- 10 RTS 4030 IFB beltpacks
- 15 RTS BP325 headset boxes
- 4 Telos One Interface
- 3 RTS TIF 2000As
- 12 Line phone system
- 6 Two-Way Radios with 2 base stations

## Graphics

- 2 VizRTs
- For- A Telestrator with HD touchscreen
- For- A Telestrator with HD touchscreen
  - 2 ST fibers required

## Engineering & Misc

- 160x352 Grass Valley Router HD-SDI
- 17 Frame sync/cross converters
  - 14 AJA FS-1s and 3 AJA FS-2s for a total of 20 paths
- TSI-3000 tally system with virtual tally
- 10 Utility cross converters
- 2 Lighting Kits

## Outboard Monitors

- Fifteen 13" Outboard LCD video monitors

## Cable

- 2875' Triax
  - Two 500', Six 250'
  - Three 5 line triax mults 125'
- 200' 10 Line video mult
  - One 100', Two 50'
- 600' 5 Line video mult
  - Four 150'
- 450' TAC singlemode fiber
  - Two 150' TAC-12, One 150' TAC-6
- 1400' SMPTE fiber
  - Four 250', Four 100'
- 1900' DT12
  - Four 250', Six 150'
- 125' Three phase power cable
  - Set of 75' and 50'
- Additional cable available if shipped separately

## Power Required

- 208 VAC, three phase, 200 amps
  - Separate 200 amps of three phase 208 VAC may be required in high heat locations

## Dual Audio Trailer/Tractor (DAT)

This equipment is available during dual feeds

- STUDER Vista 1 (32 fader)
- Enco Hotshot2 Audio Playback System
- Digicart E with ZIP drive
- CD Player
- 4 EV R50 stick mics
- 4 Sennheiser HMD sportscaster headsets
- 4 Daltech talkback boxes
- 4 RTS 4030 IFB beltpacks
- 4 RTS BP325 headset boxes
- 2 Telos One Interfaces
- 2 Lighting Kits
- 900' DT12
  - Six 150'